



D-Link EAGLE PRO AI AX1500 Smart Router trådlös router Gigabit Ethernet Dual-band (2,4 GHz / 5 GHz) Vit

Märke : D-Link
Produktkod: R15/E
Product name : EAGLE PRO AI AX1500 Smart Router

D-Link EAGLE PRO AI AX1500 Smart Router. Typ av WAN-anslutning: RJ-45. Wi-Fi-band: Dual-band (2,4 GHz / 5 GHz), Wi-Fi-standard: Wi-Fi 6 (802.11ax), Dataöverföringshastighet via WLAN (max): 1201 Mbit/s. Typ av Ethernet LAN-gränssnitt: Gigabit Ethernet, Datahastighet för Ethernet-LAN: 10,100,1000 Mbit/s, Kabelteknik: 10/100/1000Base-T(X). Kryptering/säkerhet: WPA2, WPA3, WPS. Produkttyp: Bordsrouter, Produktens färg: Vit, LED-indikatorer: LAN, Energiljus



WAN-anslutning		Bevakning	
Ethernet WAN *	✓	Föräldrakontroll	✓
DSL WAN *	✗	Filtrering	✓
SIM-kortplats *	✗	MAC-adressfiltrering	✓
Kompatibelt med 3G/4G USB-modem *	✗	Filtrering för IP-adress	✓
Typ av WAN-anslutning	RJ-45	DMZ-stöd	✓
Trådlös LAN		Design	
Wi-Fi-band *	Dual-band (2,4 GHz / 5 GHz)	Produktens färg	Vit
Wi-Fi-standard *	Wi-Fi 6 (802.11ax)	LED-indikatorer	LAN, Energiljus
Dataöverföringshastighet via WLAN (max) *	1201 Mbit/s	Produkttyp *	Bordsrouter
Wi-Fi-standarder	802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Certifikat	
Dataöverföringshastighet via WLAN (första bandet)	300 Mbit/s	Certifikat för överensstämmelse	CE, Federal Communications Commission (FCC), Industry Canada (IC)
Dataöverföringshastighet via WLAN (andra bandet)	1201 Mbit/s	Förpackningens innehåll	
Modulator	1024-QAM, OFDMA	Kabel inkluderad	LAN (RJ-45)
Nätverk		AC-adapter inkluderad	✓
Nätverksansluten (Ethernet) *	✓	Snabbstartsguide	✓
Typ av Ethernet LAN-gränssnitt *	Gigabit Ethernet	Hållbarhet	
Datahastighet för Ethernet-LAN	10,100,1000 Mbit/s	Uppfyller hållbarhetskrav	✓
Kabelteknik	10/100/1000Base-T(X)	Antenn	
Kommunikationsstandarder	IEEE 802.11a, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11h, IEEE 802.11k, IEEE 802.11n, IEEE 802.11v, IEEE 802.3ab, IEEE 802.3u	Antenndesign *	Extern
Mobilt nätverk		Antenner mängd	4
Mobilt nätverksgeneration	Stöds inte	Egenskaper	
		Fungerar med Amazon Alexa	✓
		Fungerar med Google Assistant	✓

Anslutningar		Strömtillförsel	
Antal LAN (RJ-45) anslutningar *	3	Strömkälla av typen *	DC
USB-port *	✗	Miljökrav	
Likströmsingång	✓	Temperatur vid drift	0 - 40 ° C
Management features		Temperaturintervall (förvaring)	-20 - 65 ° C
Webbaserad adminstraion	✓	Intervall för relativ operativ luftfuktighet	10 - 90%
Stöd för garanterad tjänstekvalitet (QoS)	✓	Fuktighet (förvaring)	5 - 95%
Återställningsknapp	✓	Systemkrav	
WPS tryckknapp	✓	Webbläsare stöds	Internet Explorer 10/Firefox 28.0/Chrome 28.0/Safari 6.0
Intelligent mesh-teknik	✓		Windows 10, Windows 10 Education, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64
MU-MIMO-teknik	✓	Windows-operativsystem som stöds	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma
Bevakning		Mac-operativsystem som stöds	
Kryptering/säkerhet	WPA2, WPA3, WPS		
SPI (Stateful Packet Inspection)	✓	Mobila operativsystem som stöds	
DoS-attacker	✓		
		Vikt & dimension	
		Bredd	195 mm
		Djup	139 mm
		Höjd	55 mm
		Vikt	300 g



0790069459566



790069459566

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.