



TP-Link Archer NX600 trådløs ruter Gigabit Ethernet Dobbelbånd (2.4 GHz / 5 GHz) 5G Hvit

Merke : TP-Link

Product family: Archer

Produktkode: ARCHER NX600

Produkt navn : Archer NX600

TP-Link Archer NX600. WAN tilkoblingstype: RJ-45. Wi-Fi-bånd: Dobbelbånd (2.4 GHz / 5 GHz), Beste Wi-Fi-standard: Wi-Fi 6 (802.11ax), Wi-Fi-standarder: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Ethernet LAN-grensesnitttype: Gigabit Ethernet, Ethernet LAN dataoverføringshastigheter: 10,100,1000,2500 Mbit/s, Maksimal Tx-effekt (2,4 GHz): 20 dBmW. Mobilnettverksgenerasjon: 5G, 3G-standarder: DC-HSDPA, HSPA, HSPA+, UMTS, 4G standard: LTE-TDD & LTE-FDD. Sikkerhetsalgoritmer: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK



WAN forbindelse		Sikkerhet	
Ethernet WAN *	✓	URL-filtrering	✓
DSL WAN *	✗	DMZ støttes	✓
SIM-kortspor *	✓	Protokoller	
WAN tilkoblingstype	RJ-45	DHCP-klient	✓
Trådløse internett-funksjoner		DHCP-server	✓
Wi-Fi-bånd *	Dobbelbånd (2.4 GHz / 5 GHz)	Universal Plug and Play (UPnP)	✓
Beste Wi-Fi-standard *	Wi-Fi 6 (802.11ax)	Støttede nettverksprotokoller	IPv4, IPv6
Wi-Fi-standarder	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Design	
Nettverksbygging		Produktfarge	Hvit
Ethernet/bredbåndsforbindelse *	✓	Sertifkater	
Ethernet LAN-grensesnitttype *	Gigabit Ethernet	Samsvarssertifikat	CE, RoHS
Ethernet LAN dataoverføringshastigheter	10,100,1000,2500 Mbit/s	Emballasjeinnhold	
Portvideresending	✓	Kabler inkludert	LAN (RJ-45)
Portutløsning	✓	AC-adapter bunt	✓
Dynamisk DNS (DDNS)	✓	Guide for hurtiginstallering	✓
Antall gjestenettverk (2.4 GHz)	1	Antenne	
Antall gjestenettverk (5 GHz)	1	Antennedesign *	Innvendig og utvendig
Maksimal Tx-effekt (2,4 GHz)	20 dBmW	Antennetilkoblingstype	SMA
Maksimal Tx-effekt (5 GHz)	30 dBmW	Antall antenner	14

Mobilt nettverk		Energihåndtering	
Mobilnettverksgenerasjon	5G	AC-inngangsspenning	100 - 240 V
3G-standarder	DC-HSDPA, HSPA, HSPA+, UMTS	AC-inngangsfrekvens	50/60 Hz
4G standard	LTE-TDD & LTE-FDD	Utgangsstrøm	12 V
5G-bånd støttes	700,800,850,900,1800,2100,2300,2500,2600,3500,3700 MHz	Utgangsstrøm	2 A
4G-båndet støttes	700,800,850,900,1800,2100,2300,2500,2600,3500,3700 MHz	Miljømessige forhold	
3G-båndet støttes	850,900,2100 MHz	Driftstemperatur (T-T)	0 - 40 °C
SIM-korttype	NanoSIM	Oppbevaringstemperaturomåde (Celsius)	-40 - 70 °C
Styringsfunksjoner		Relativ luftfuktighet under drift (H-H)	10 - 90%
Wi-Fi Multimedia (WMM)/(WME)	✓	Lagringsrelativ fuktighet	5 - 90%
Quality of Service (QoS) støtte	✓	Systemkrav	
Tilbakestillingsknapp	✓	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows RT 8.1, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
WPS-trykknapp	✓	Støttede Linux operativsystemer ✓	
Sikkerhet		Støttede Mac operativsystemer ✓	
Sikkerhetsalgoritmer	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Kompatibel med Mac ✓	
Gjeste-inngang	✓	Vekt og dimensjoner	
DoS-angrepsbeskyttelse	✓	Bredde	99 mm
Foreldrestyring	✓	Dybde	99 mm
Filtrering	✓	Høyde	190 mm
IP-adressefiltrering	✓		



8885020624878



8885021371610

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.