TP-Link Deco X50-5G Dobbelbånd (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Hvit 3 Innvendig lys





Merke : TP-Link

Produktkode: DECO X50-5G(1-PACK)

Produktnavn : Deco X50-5G

TP-Link Deco X50-5G. Produktfarge: Hvit, Antennetype: Innvendig lys, Produkttype: Mesh system. Wi-Fi-bånd: Dobbelbånd (2.4 GHz / 5 GHz), Beste Wi-Fi-standard: Wi-Fi 6 (802.11ax), WLAN data overførings rate (max): 2402 Mbit/s. Mobilnettverksgenerasjon: 5G, 4G standard: LTE-TDD & LTE-FDD. Støttede nettverksprotokoller (IPv6): IPv4/IPv6. Sertifisering: RoHS, CE, RCM

Design	
Produkttype	Mesh system
Produktfarge *	Hvit
Antennetype *	Innvendig lys
Antall antenner	2
Maksimal dekningsevne	230 m²

Trådløse internett-funksjoner	
Wi-Fi-bånd *	Dobbelbånd (2.4 GHz / 5 GHz)
Beste Wi-Fi-standard *	Wi-Fi 6 (802.11ax)
Wi-Fi-standarder	802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
WLAN data overførings rate (max) *	2402 Mbit/s
WLAN dataoverføringshastighet (første band)	2402 Mbit/s
WLAN dataoverføringshastighet (andre band)	574 Mbit/s
Nettverksstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Sikkerhetsalgoritmer	WPA, WPA2, WPA3
Antall gjestenettverk (5 GHz)	1
Antall gjestenettverk (2.4 GHz)	1
Point-to-point protocol over Ethernet (PPPoE)	✔
Dynamisk IP	✔
Statisk IP	✔
WDS-bro	✔
IGMP-proxy	✔
IGMP-snooping	✔

Egenskaper	
Quality of Service (QoS) støtte	✔
DHCP-klient	✔
DHCP-server	✔
Universal Plug and Play (UPnP)	✔
MU-MIMO-teknologi	✔
MIMO	✔

Protokoller	
Støttede nettverksprotokoller (IPv6)	IPv4/IPv6

Tilkoblingsevne	
Antall ethernets-/bredbåndstilkoblinger (RJ-45) *	3
Ethernet WAN	✔

Sertifikater	
Sertifisering	RoHS, CE, RCM

Miljømessige forhold	
Driftstemperatur (T-T)	0 - 40 °C
Oppbevaringstemperaturområde (Celsius)	-40 - 60 °C
Relativ luftfuktighet under drift (H-H)	10 - 90%
Lagringsrelativ fuktighet	5 - 90%

Vekt og dimensjoner	
Bredde	130 mm
Dybde	123 mm
Høyde	210,5 mm

Trådløse internett-funksjoner	
Tagget VLAN	✔
Dynamisk DNS (DDNS)	✔
Støttede kontrollprogrammer	TP-Link Deco

Mobilt nettverk	
Mobilnettverksgenerasjon	5G
4G standard	LTE-TDD & LTE-FDD

Emballasjeinnhold	
AC-adapter bunt	✔
Ethernet-kabel	✔

Datainnpakking	
Pakkebredde	237 mm
Pakkedybde	276,5 mm
Pakkehøyde	147,5 mm
Pakkevekt	1,64 kg

4897098687949

4897098687826

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-JUN-2026. Prints or copies of Information are only valid on the printed Publication date